

97108 (9-38,137)

PNEUMATIC RADIAL TIRE FOR ALL-SEASON PASSENGER CAR

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to a pneumatic tire and more particularly to a pneumatic radial tire for all-season passenger car.<sup>use</sup>

Description of Related Art

As shown in Fig. 3, the conventionally typical pneumatic radial tire for all-season passenger car<sup>use</sup> had a tread pattern in which many blocks were formed at given intervals in an axial direction and<sup>in</sup> a circumferential direction of the tire by a plurality of circumferential grooves straightforward extending in the circumferential direction and a plurality of slant grooves each extending at an inclination angle of about 45° with respect to the circumferential direction.

In this type of the pneumatic radial tire for all-season passenger car,<sup>use</sup> it is required to have various performances such as drainage property in the<sup>while</sup> running on<sup>a</sup> wet road surface, steering stability<sup>while</sup> ~~in the~~ running on<sup>a</sup> dry road surface, snow performances in the running on snow, e.g. braking performance, traction performance, straight running performance, cornering performance and the like, resistance to uneven wear and so on.

Recently, it is demanded to develop pneumatic radial tires for all-season passenger car developing an excellent drainage property in the running on wet road surface without

a substantially sacrificing the steering stability<sup>while</sup> ~~in the~~  
a running on<sup>a</sup> dry road surface, the snow performances and the  
resistance to uneven wear.

SUMMARY OF THE INVENTION

5 It is, therefore, an object of the invention to  
provide a pneumatic radial tire for all-season passenger car<sup>use</sup>  
a having an excellent drainage property<sup>while</sup> ~~in the~~ running on wet  
a road surface<sup>s</sup> without degrading various performances of the  
conventional pneumatic radial tire for all-season passenger  
a 10 car<sup>use</sup>, particularly the steering stability<sup>while</sup> ~~in the~~ running on<sup>a</sup>  
dry road surface, the snow performances and the resistance  
to uneven wear.

a According to the invention, there is the provision<sup>use</sup>  
of in a pneumatic radial tire for all-season passenger car<sup>use</sup>  
15 comprising a tread with a tread pattern defined by dividing  
the tread into many blocks through a plurality of slant  
grooves arranged at given intervals in a circumferential  
direction of the tire and at least one circumferential  
center groove extending in the circumferential direction of  
20 the tire at a center of the pattern, and consisting of a  
central zone having a width corresponding to 30-60% of a  
tread width and a pair of side zones located on both sides  
a of the central zone, ~~the improvement wherein~~  
(1) the slant grooves comprise steeply slant grooves  
25 extending at a relatively small inclination angle with  
respect to the circumferential direction and gently slant  
grooves extending at a relatively large inclination angle  
with respect to the circumferential direction;

a (2) the steeply slant groove <sup>are</sup> ~~is~~ opened to the circumferential center groove in the central zone of the tread, while  
a the gently slant groove <sup>are</sup> ~~is~~ opened to a tread end in each of both side zones of the tread;

5 (3) the number of the gently slant grooves is made two times or more than the number of the steeply slant grooves so that an interval between the gently slant grooves in the circumferential direction is made  $1/2$  or less than an  
10 interval between the steeply slant grooves in the circumferential direction;

(4) each of the blocks is provided with at least one side; and

a 15 (5) each of the blocks defined by the circumferential center groove and the steeply slant grooves is chamfered from a tapered top end over a range of 10-30 mm <sup>in</sup> ~~toward~~ a longitudinal direction of the block so as to gradually shallow a depth of a surface of the block from the tapered top end <sup>in</sup> ~~toward~~ the longitudinal direction.

a 20 In preferable embodiments of the invention, the steeply slant groove extends at an inclination angle of  $10^{\circ}$ - $50^{\circ}$  with respect to the circumferential direction <sup>and</sup> ~~and~~  
a <sup>The</sup> ~~the~~ gently slant groove extends at an inclination angle of  $60^{\circ}$ - $90^{\circ}$  with respect to the circumferential direction <sup>and</sup> ~~and~~  
a <sup>The</sup> ~~the~~ chamfered surface of the block is a curved surface  
25 having a radius of curvature of 10-100 mm <sup>and</sup> ~~and~~ <sup>T</sup> ~~the~~ steeply slant groove ~~is~~ communicated <sup>S</sup> with the gently slant groove.

a In <sup>other</sup> ~~another~~ preferable embodiments of the invention, a circumferential side groove extending in the circumferential

direction of the tire is arranged in a position separated inward from the tread end at about 1/4 of the tread width in an axial direction of the tire, and the gently slant groove is opened to the circumferential side groove.

a 5 In ~~the~~ other preferable embodiments of the invention, the extending direction of the side formed in the block differs between the central zone and the side zone of the tread, and the sipe formed in the blocks at both side zones of the tread extends in parallel to or substantially in  
10 parallel to the gently slant groove to be opened to the circumferential side groove, ~~and~~ <sup>I</sup> the sipe formed in the block at the central zone of the tread is opened to the steeply slant groove at a cross angle of not less than 45°.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15 The invention will be described with reference to the accompanying drawings, wherein:

Fig. 1 is a partly enlarged plan view of a first embodiment of the tread pattern in the pneumatic radial tire according to the invention;

20 Fig. 2 is a partly enlarged plan view of a second embodiment of the tread pattern in the pneumatic radial tire according to the invention; and

Fig. 3 is a partly enlarged plan view of a tread pattern in the conventional pneumatic radial tire.

#### DESCRIPTION OF PREFERRED EMBODIMENTS

25 In the pneumatic radial tire according to the invention having the above structure, at least one circumferential center groove extending in the circumferential

a direction of the tire is particularly arranged in the center  
of the pattern, <sup>T</sup>and the steeply slant groove arranged in the  
central zone of the tread and opening to the circumferential  
a center groove <sup>S</sup>is communicated with the gently slant groove  
5 arranged in each side zone of the tread and opening to the  
tread end, so that the draining action is smoothly carried  
a out from the pattern center toward the tread end <sup>T</sup>and <sup>H</sup>hence  
there is obtained a pneumatic radial tire having an  
excellent drainage property in the running on wet road  
10 surface. However, a tapered top end portion is formed in  
each of the blocks defined by the circumferential center  
groove and the steeply slant grooves, so that there may be  
caused a tendency of extremely degrading the steering  
stability in the running on dry road surface and the  
15 resistance to uneven wear due to the lacking of block  
rigidity.

Furthermore, each of the blocks defined by the  
circumferential center groove and the steeply slant grooves  
is chamfered from the tapered top end over a range of 10-30  
20 mm toward the longitudinal direction of the block so as to  
gradually shallow the depth of the block surface from the  
tapered top end toward the longitudinal direction as  
a mentioned above. <sup>Consequently</sup>so that the branching of water flow is  
smoothly carried out to control or prevent the occurrence of  
25 air bubbles due to turbulence and to improve the drainage  
property of the tire. In this case, the block rigidity is  
ensured, so that there is not caused the extreme degradation  
of the steering stability in the running on dry road surface

and the resistance to uneven wear. Preferably, the chamfered surface of the block is a curved surface having a radius of curvature of 10-100 mm, so that the resistance of water can efficiently be decreased and also ~~the~~ crushing can be suppressed to obtain a high ground contact pressure and hence ensure the steering stability.

<sup>Additionally</sup>  
~~And also,~~ the number of the gently slant grooves is made two ~~times~~ <sup>times</sup> or more ~~than~~ the number of the steeply slant grooves so that an interval between the gently slant grooves in the circumferential direction is made 1/2 or less than an interval between the steeply slant grooves in the circumferential direction as mentioned above. <sup>As a result</sup> ~~so that~~ the interval between the gently slant grooves in the circumferential direction is relatively large in the central zone of the tread including the steeply slant grooves and hence ~~the~~ block rigidity is ensured. <sup>The</sup> ~~while the~~ interval between the gently slant grooves in the circumferential direction is relatively small in each of both side zones of the tread including the gently slant grooves and hence the drainage property <sup>while</sup> ~~in the~~ running on <sup>a</sup> wet road surface, pitch variation effect for controlling the pattern noise and the resistance to uneven wear (heel and toe wear) are improved.

Moreover, at least one sipe is formed in each of the blocks, so that the snow performances as an all-season tire and the gripping performance <sup>s. while</sup> ~~in the~~ running on wet road surface are ensured. When the extending direction of the side formed in the block differs between the central zone and the side zone of the tread, the directionality of block

rigidity in the tread pattern can be denied to suppress the occurrence of bad steering control and uneven wear (diagonal wear). <sup>moderately</sup> ~~And also~~, the side formed in the block at the

central zone of the tread is opened to the steeply slant groove at a cross angle of not less than  $45^\circ$ , so that the resistance to uneven wear is improved.

The following examples are given in illustration of the invention and are not intended as limitations thereof.

In Fig. 1 is shown a tread pattern of the pneumatic radial tire according to the invention having a tire size of 205/60R15 and a tread width TW of 160 mm as Example 1.

As shown in Fig. 1, the tread of this tire comprises a central zone TC having a width corresponding to 45% of the tread width TW and a pair of side zones TS located on both sides of the central zone TC. <sup>The tire</sup> ~~and~~ has a tread pattern defined by dividing the tread into many blocks 3 through a plurality of slant grooves 1, 2 arranged at given intervals in a circumferential direction of the tire and two circumferential center grooves 4 extending in the circumferential direction of the tire at a center <sup>portion</sup> of the pattern.

The slant grooves 1, 2 comprise steeply slant grooves 1 extending at a relatively small inclination angle of  $20^\circ$ - $40^\circ$  with respect to the circumferential direction and gently slant grooves 2 extending at a relatively large inclination angle of  $70^\circ$ - $80^\circ$  with respect to the circumferential direction. The steeply slant grooves 1 are arranged in the central zone TC of the tread and <sup>are</sup> ~~are~~ opened to the circumferential center groove 4, while the gently slant

grooves 2 are arranged in each of the side zones TS in the tread and <sup>are</sup> opened to an end TE of the tread.

The gently slant grooves 2 are arranged in <sup>a</sup>the number larger by two times than that of the steeply slant grooves 1 in such a manner that the interval between the gently slant grooves 2 in the circumferential direction is 1/2 of the interval between the steeply slant grooves in the circumferential direction. Further, the steeply slant groove 1 ~~is~~ <sup>s</sup>communicated with the gently slant groove 2.

10 In this case, since the number of the gently slant grooves 2 is larger by two times than the number of the steeply slant grooves 1, all of the steeply slant grooves 1 are communicated with only half of the total gently slant grooves 2.

15 A circumferential side groove 5 extending in the circumferential direction is arranged in a position separated inward from the tread end TE by about 1/4 of the tread width TW in an axial direction of the tire. The gently slant groove 2 ~~is~~ <sup>s</sup>opened to the circumferential side groove 5.

20 At least one sipe 6 is formed in each of the blocks 3, in which the extending direction of the sipe 6 in the block 3 is upward <sup>and</sup> to the right in the central zone TC of the tread and upward to the left in both side zones TS of the tread as shown in Fig. 1. Further, the sipe 6 formed in the block 3 at each of the side zones TS extends in parallel to or  
25 substantially in parallel to the gently slant groove 2 and ~~is~~ <sup>s</sup>opened to the circumferential side groove 5, while the sipe 6 formed in the block 3 at the central zone TC is



opened to the steeply slant groove 1 at a cross angle of not less than  $45^\circ$ .

a  
r 5 Each of the blocks 3 defined by the circumferential center groove<sup>s</sup> 4 and the steeply slant grooves 1 is chamfered from the tapered top end over 25 mm<sup>n</sup> toward the longitudinal direction of the block so as to gradually shallow the depth of the block surface from the tapered top end toward the longitudinal direction as mentioned above, and the chamfered surface of the block is a curved surface having a radius of curvature of about 30 mm.  
10

In Fig. 2 is shown a tread pattern of the pneumatic radial tire according to the invention having a tire size of 205/60R15 and a tread width TW of 160 mm as Example 2.

As shown in Fig. 2, the tread of this tire comprises  
15 a central zone TC having a width corresponding to 45% of the tread width TW and a pair of side zones TS located on both sides of the central zone TC and has a tread pattern defined by dividing the tread into many blocks 3 through a plurality of slant grooves 1, 2 arranged at given intervals in a  
20 circumferential direction of the tire and two circumferential center grooves 4 extending in the circumferential direction of the tire at a center<sup>portion</sup> of the pattern.

a  
25 The slant grooves 1, 2 comprise steeply slant grooves 1 extending at a relatively small inclination angle of  $20^\circ$ - $40^\circ$  with respect to the circumferential direction and gently slant grooves 2 extending at a relatively large inclination angle of  $70^\circ$ - $80^\circ$  with respect to the circumferential direction. The steeply slant grooves 1 are arranged

a in the central zone TC of the tread and opened to the circumferential center groove 4, while the gently slant grooves 2 are arranged in each of the side zones TS in the tread and opened to an end TE of the tread.

a  
5 The gently slant grooves 2 are arranged in <sup>a</sup>the number larger by two times than that of the steeply slant grooves 1 in such a manner that the interval between the gently slant grooves 2 in the circumferential direction is 1/2 of the interval between the steeply slant grooves in the circumferential direction. Further, the steeply slant groove 1 ~~is~~ <sup>s</sup>communicated with the gently slant groove 2. In this case, since the number of the gently slant grooves 2 is larger by two times than the number of the steeply slant grooves 1, all of the steeply slant grooves 1 ~~are~~ <sup>s</sup>communicated with only half of the total gently slant grooves 2.

a  
10  
15

a  
A circumferential side groove 5 extending in the circumferential direction is arranged in a position separated inward from the tread end TE by about 1/4 of the tread width TW in an axial direction of the tire. The gently slant groove 2 is opened to the circumferential side groove 5.

20

At least one sipe 6 is formed in each of the blocks 3, in which the sipe 6 is arranged in only the block 3 located in both side zones TS and is not arranged in the block 3 located in the central zone TC as shown in Fig. 2.

25 Each of the blocks 3 defined by the circumferential center groove 4 and the steeply slant grooves 1 is chamfered from the tapered top end over 25 mm toward the longitudinal direction of the block so as to gradually shallow the depth

of the block surface from the tapered top end toward the longitudinal direction as mentioned above, and the chamfered surface of the block is a curved surface having a radius of curvature of about 30 mm.

5 *a* In Fig. 3 <sup>illustrates</sup> ~~is shown~~ a tread pattern of a pneumatic radial tire as a conventional example.

The tread of such a conventional tire has a tread pattern defined by dividing the tread into many blocks through five circumferential grooves extending straightforward 10 in the circumferential direction and a plurality of slant grooves extending at an inclination angle of about 45° with respect to the circumferential direction.

*a* A <sup>J</sup> test for evaluating the drainage property in the running on wet road surface, the steering stability on dry road surface, the snow performances and the resistance to uneven wear <sup>was</sup> ~~are~~ carried out with respect to the tires of Examples 1 and 2 and <sup>a</sup> conventional example. 15

*a* The drainage property in the running on <sup>a</sup> wet road surface is evaluated by <sup>a</sup> driver's feeling on a hydroplaning limit speed when the tire is run on <sup>a</sup> wet road surface having a water depth of 5 mm, and the steering stability on dry road surface is evaluated by <sup>a</sup> driver's feeling when the tire is run on a circuit course at various sport running modes, and the snow performances are total feeling 20 *a*

25 evaluation of braking performance, traction performance, straight running performance and cornering performance on a pressed snow road surface of a test course, and the resistanc to uneven wear is totally evaluated by visual

evaluation of worn shape when the tire is run on roads including an expressway, a mountain slope and streets over a distance of 10,000 km and measurement of step difference between adjoining blocks.

- 5           The test results are shown in Table 1, in which each of the properties is represented by an index on the basis that the conventional tire is 100. The larger the index value, the better the property.

Table 1

| Tire                      | Example 1 | Example 2 | Conventional Example |
|---------------------------|-----------|-----------|----------------------|
| Drainage property         | 120       | 140       | 100                  |
| Steering stability        | 100       | 105       | 100                  |
| Snow performances         | 105       | 90        | 100                  |
| Resistance to uneven wear | 100       | 100       | 100                  |

As mentioned above, according to the invention, there are provided pneumatic radial tires developing an excellent drainage property in the running on wet road surface without degrading the steering stability in the running on dry road surface, the snow performances and the resistance to uneven wear.